

DATA SHEET

irudek



- 1** **LIGHTWEIGHT:** ITS 2 METERS AND THE MINI DESIGN MAKE THE WEIGHT ON THE BACK HARDLY NOTICEABLE WHEN WORKING WITH A TWINBLOK
- 2** **ROBUST:** HIGH-STRENGTH SYNTHETIC HOUSING, OFFERING LONG DURABILITY
- 3** **SAFE:** REDUCES IMPACT FORCE TO BELOW 6KN
- 4** **SWIVEL RING:** DESIGNED TO BE ABLE TO MAKE CONNECTIONS WITH TWINCONNECT
- 5** **ENERGY ABSORBER WITH PROTECTOR:** FOR HORIZONTAL WORK WITH THE POSSIBILITY OF VERTICAL FALL ON SHARP EDGES, ACCORDING TO VG 11. 060..
- 6** **CERTIFIED FOR GROUND ANCHORING FACTOR 2**
- 7** **COMFORTABLE:** OFFERS CONTINUOUS SAFETY WITHOUT OBSTACLES, AVOIDING UNNECESSARY SNAGGING AND FALLING

MINIBLOK H

These devices stand out for their simplicity of use, avoiding the need for specific knowledge. The operation is very simple, the device provides the user with the necessary meters for its work, being always in tension, avoiding any fall. They have mechanical braking, achieving fast and safe braking.

Material	
Tape	Technora® 21mm
Housing	Syntetic
Conectors	Aluminium

Norm	EN 360, VG11,060:2014
Length	2 m
Weight	1,2 Kg
Stopping distance	1,2 m
Height	570 mm
Length	55,6 mm
Width	87,3 mm
Load	140 Kg
Static resistance	15 kN
Twinconnect Resistance	< 6 kN
Impact power	10 of use + 1 of storage