

Prod. Ref.	18550-000
Safety cat.	S3 SRC
Range of sizes	39 - 48 (6 - 13)
Weight (sz. 8)	530 g
Shape	B
Width	11

Description: Black water repellent Pull-Up Nubuck ankle boot, **SANY-DRY®** lining, antistatic, anti-shock, slipping resistant, non metallic **APT Plate** midsole **Zero Perforation**

Plus: FOOT-PAD footbed, extremely soft and comfortable footbed. Thanks to the very low density polyurethane, the footbed is self-molding granting a right distribution of the body weight and providing an immediate feeling of comfort. High shock absorption is provided from highly resilient material and a perfect cushion in the central area of the heel. Perfumed sole. **TPU toe cap protection**

Suggested uses: Construction, maintenance, industries

Care and maintenance: Clean after each use and dry off away from direct heat. Avoid contact with aggressive chemicals or extreme temperature. Avoid immersion in sea water, lime water or cement mixed with water



MATERIALS / ACCESSORIES

SAFETY TECHNICAL SPECIFICATIONS

		Clause EN ISO 20345:2011	Description	Unit	Cofra result	Requirement
Complete shoe	Toe cap: ALUMINIUM made, ultra light, impact resistant until 200 J and compression resistant until 1500 kg	5.3.2.3	Shock resistance (clearance after shock)	mm	15	≥ 14
		5.3.2.4	Compression resistance (clearance after compression)	mm	18	≥ 14
	Anti perforation midsole: in multi-layers highly tensile fabric, penetration resistant, Zero Perforation	6.2.1	Penetration resistance	N	To 1100 N	≥ 1100
					No perforation	
Upper	Antistatic shoe: the bottom is fit for the dissipation of electrostatic charges	6.2.2.2	Electric resistance			
			- wet	MΩ	79,6	≥ 0.1
	Energy absorption system		- dry	MΩ	325	≤ 1000
		6.2.4	Shock absorption	J	26	≥ 20
	Black water repellent Pull-Up Nubuck thickness 1,8//2,0 mm	5.4.6	Water vapour permeability	mg/cmq h	> 4,1	≥ 0,8
			Permeability coefficient	mg/cmq	> 50,5	> 15
		6.3.1	Water resistance	minutes	10%	≤ 30%
					0,0 g	≤ 0,2 g
	Vamp	5.5.3	Water vapour permeability	mg/cmq h	> 4,7	≥ 2
			Permeability coefficient	mg/cmq	> 40,6	≥ 20
Quarter lining	SANY-DRY® , breathable, abrasion resistant, colour silver thickness 1,2 mm	5.5.3	Water vapour permeability	mg/cmq h	> 10,3	≥ 2
			Permeability coefficient	mg/cmq	> 82,8	≥ 20
	Antistatic Polyurethane/TPU directly injected in the upper:	5.8.3	Abrasion resistance (lost volume)	mm ³	89	≤ 150
		5.8.4	Flexing resistance (cut increase)	mm	1,6	≤ 4
	Outsole: ice TPU, slipping resistant, abrasion resistant and hydrocarbons resistant.	5.8.5	Interlayer bond strength	N/mm	3,1	≥ 3
		6.4.2	Hydrocarbons resistance (ΔV = volume increase)	%	6,5	≤ 12
	Midsole: black polyurethane, low density, comfortable and anti-shock.	5.3.5	SRA : ceramic + detergent solution – flat		0,37	≥ 0,32
			SRA : ceramic + detergent solution – heel (contact angle 7°)		0,30	≥ 0,28
			SRB : steel + glycerol – flat		0,47	≥ 0,18
			SRB : steel + glycerol – heel (contact angle 7°)		0,23	≥ 0,13
	Adherence coefficient of the sole					